



F O C U S 7
(FORMERLY ALX7)



UNDERCABINET TASK LIGHTING

SPECIFICATIONS

HOUSING

Extruded aluminum housing up to 12' long.

FINISH

Satin anodized or white paint finish standard. RAL powdercoat and medical/antimicrobial optional.

LENS

Extruded DR acrylic, snap-on frosted widespread lens. No Pixelization

LED DRIVER

Integral, universal voltage; 0-10V dimming standard; 1% or 10% dimming. 2 Wire Driver Optional

K/O's

1/2" K/O on both ends standard, or field drilled as required.

MOUNTING

Surface Mount: Mounting holes pre-drilled.

LED's


60,000 hours. (L70), High uniformity 80 CRI.

CERTIFICATION


ETL/CSA listed for damp locations.



OPTICS



COUNTER TOP LIGHT UP



MAINLY BACKSPLASH LIGHT UP

OPTIONS



SW120 – SWITCH 120V
SW277 – SWITCH 277V
HLSW – HI/LO SWITCH



DU – DUPLEX OUTLET
Grounded 15A Convenience Outlet



USB – DUAL USB OUTLET
Grounded 15A Convenience Outlet



PC – 6' POWER CORD
18/3 Cord with U Ground Plug. White Standard (For Non-Dim)



MS MOTION SENSOR



FOCUS 7