




LED SQUARES / CABLE SUSPENDED / SURFACE MOUNT




PROJECT:

TYPE:


SPECIFICATIONS

DESCRIPTION	Architectural LED squares, available with down light, up light, inside light or outside light options.
HOUSING	Extruded aluminum housing, 2" wide.
FINISH	Satin anodized or white paint finish standard. Custom finish optional.
LENS	Three styles (see page 2); White frosted acrylic, smooth uniformity and no pixelization.
LED DRIVER	Integral or remote (<i>Included</i>), universal voltage; 0-10V dimming standard; custom programmable.
MOUNTING	Cable suspended and surface mount: See page 3 for details and options.
LED's	(LED boards) 50,000 hours. (L70), 80 CRI, 2700K, 3000K, 3500K and 4000K.
CERTIFICATION	ETL/CSA listed for damp locations.  2001431  MADE IN THE USA


OPTIONS




Q2 - DL - DOWN LIGHT



Q2 - UL - UP LIGHT



Q2 - IL - INSIDE LIGHT



Q2 - OL - OUTSIDE LIGHT

PART NUMBER


SERIES	LUMENS	COLOR	LENS	VOLTS	DRIVER	MOUNTING	CABLE	FINISH	FIXTURE SIZE
Q2 - DL	L LOW	27K 2700K	SQL SQUARE	UNV (120/277) 10% DIM	I INTEGRAL	SC STRAIGHT CABLE	36"	S SATIN	2' X 2'
Q2 - UL	M MEDIUM	3K 3000K	RLR ROUND	UNV 1% (120/277) 1% DIM	R REMOTE	PC PYRAMID CABLE	48"	W WHITE	3' X 3'
Q2 - IL	H HIGH	35K 3500K	FL FLAT			CC CENTER CABLE	72"	C CUSTOM	4' X 4'
Q2 - OL	CP CUSTOM PROGRAMMED (Specify Lumens/FT or Watts/FT)	4K 4000K				SM SURFACE			OTHER (SPECIFY)

LUMENS & LED COLOR OPTIONS


	SQ SIZE	WATTS	2700K	3000K	3500K	4000K
LOW LUMENS	2' SQ	28W	4000 L	4240 L	4280 L	4480 L
	3' SQ	42W	6000 L	6360 L	6420 L	6720 L
	4' SQ	56W	8000 L	8480 L	8560 L	8960 L
MEDIUM LUMENS	2' SQ	52W	6960 L	7320 L	7360 L	7760 L
	3' SQ	78W	10440 L	10980 L	11040 L	11640 L
	4' SQ	104W	13920 L	14640 L	14720 L	15520 L
HIGH LUMENS	2' SQ	72W	9280 L	9760 L	9800 L	10320 L
	3' SQ	108W	13920 L	14640 L	14700 L	15480 L
	4' SQ	144W	18560 L	19520 L	19600 L	20640 L

Higher lumen packages available.


LENS OPTIONS



SQL - SQUARE LENS



RLR - ROUND LENS



FL - FLAT LENS

REMOTE LED DRIVERS WITH ENCLOSURE *(Included)*

Universal Voltage (120/277) 0-10V Dimming Standard
Remote LED drivers recommended for easy maintenance.



WATTS

1 - 50W

2 - 50W

1 - 85W

2 - 85W

ENCLOSURE DIMENSIONS

16" X 2" x 1 1/4"

28" X 2" x 1 1/4" (ENCLOSURE W/ TWO DRIVERS)

18" X 2" x 1 1/4"

34" X 2" x 1 1/4" (ENCLOSURE W/ TWO DRIVERS)


20' Max Remote Driver Distance

The chart below shows watts / fixture and driver requirements.

Some medium and high lumen fixtures require more than one driver; Refer to chart below.


SQUARE SIZE	LOW LUMENS		MEDIUM LUMENS		HIGH LUMENS	
	WATTS	DRIVERS REQUIRED	WATTS	DRIVERS REQUIRED	WATTS	DRIVERS REQUIRED
2' X 2'	31W	1 - 50W	63W	1 - 85W	92W	2 - 50W
3' X 3'	47W	1 - 50W	95W	2 - 50W	138W	2 - 85W
4' X 4'	62W	1 - 85W	126W	2 - 85W	184W	4 - 50W

MOUNTING OPTIONS




SC – STRAIGHT CABLES STYLE

Suspension Kit includes:
 (1) 5" Round Canopy with Mounting Hardware
 (3) Top Fittings for 1/4-20 Rod with Small 2" Canopy
 (1 or 2) Prewired 18/2 or 18/5 White Power Cord
 (4) Aircraft Cables 36", 48" or 72"
 (4) Adjustable Bottom Fittings



PC – PYRAMID CABLES STYLE


Suspension Kit includes:
 (1) 5" Round Canopy with Mounting Hardware
 (1 or 2) Prewired 18/2 or 18/5 White Power Cord
 (1) Center Cable Fitting
 (4) Aircraft Cables 36", 48" or 72"
 (4) Adjustable Bottom Fittings



CC – CENTER CABLE STYLE

Suspension Kit includes:
 (1) 5" Round Canopy with Mounting Hardware
 (1) Center Aircraft Cable 24" Std.
 (1 or 2) Prewired 18/2 or 18/5 White Power Cord
 (1) Center Cable Fitting
 (4) Aircraft Cables 36", 48" or 72"
 (4) Adjustable Bottom Fittings

* Note: Fixture can rotate due to the flow of air in a given area.



SM – SURFACE MOUNT

- ⊕ 1/4" Mounting Holes Provided
- ⊗ 1/2" Service Hole Provided for Snap in Connector


* Position of mounting holes may vary; Consult Factory

FIXTURE SIZES

	2' SQUARE		3' SQUARE		4' SQUARE	
	NOMINAL SIZE	ACTUAL SIZE	NOMINAL SIZE	ACTUAL SIZE	NOMINAL SIZE	ACTUAL SIZE
DOWN LIGHT	2' X 2'	24 3/4" X 24 3/4"	3' X 3'	35 1/2" X 35 1/2"	4' X 4'	46 3/4" X 46 3/4"
UP LIGHT	2' X 2'	24 3/4" X 24 3/4"	3' X 3'	35 1/2" X 35 1/2"	4' X 4'	46 3/4" X 46 3/4"
INWARD LIGHT	2' X 2'	25 3/4" X 25 3/4"	3' X 3'	36 1/2" X 36 1/2"	4' X 4'	47 3/4" X 47 3/4"
OUTWARD LIGHT	2' X 2'	26 1/2" X 26 1/2"	3' X 3'	37" X 37"	4' X 4'	47 3/4" X 47 3/4"

* Outside dimension is 7/8" less with FL lens. Other sizes and rectangles available; Consult Factory

PHOTOMETRICS / CANDELA DISTRIBUTION Photometrics available online or by calling the factory.




SQL – SQUARE LENS

POLAR GRAPH

REPORT NO.: 103499092LAX-001

Based on 4' linear fixture at high lumens (35K 1076L/FT x 4' = 4304L)

17216 L / 4'Square




RLR – ROUND LENS

POLAR GRAPH

REPORT NO.: 103499092LAX-002

Based on 4' linear fixture at high lumens (35K 1076L/FT x 4' = 4304L)

17216 L / 4'Square



FL – FLAT ROUND LENS

POLAR GRAPH

REPORT NO.: 103499092LAX-003

Based on 4' linear fixture at high lumens (35K 1076L/FT x 4' = 4304L)

17216 L / 4'Square

SPECIFICATIONS ARE SUBJECT TO CHANGE DUE TO CONTINUOUS ADVANCES IN TECHNOLOGY
PRIMUS LIGHTING, INC. ALL RIGHTS RESERVED